



HANDELSKETTING  
COMMERCIAL  
CHAIN

**Roestvast stalen ketting**  
**Stainless chain**

**Roestvast stalen ketting / kortschalmig**  
**Stainless chain / short link**

| DIN 766 / AISI-316 / niet voor hijsdoeleinden  
| DIN 766 / AISI-316 / not for lifting applications



d = diameter  
d = diameter

mbl = minimum breekkracht  
mbl = minimum breaking load


LB = lengte per bos  
LB = length per bundle

Artikelnr.	d	a	b	mbl	mbl	LB	kg/100m
Part no.	mm	mm	mm	kN	kg	m	kg/100m
31500502	2	12	5	1,3	130	50.	7
31500503	3	16	5	4,5	460	50	16,7
31500504	4	16	6	8	815	50	32
31500505	5	18,5	7	12,5	1.275	50	50
31500506	6	18,5	8	18	1.835	50	75
31500508	8	24	10	32,1	3.270	50	135
31500510	10	28	14	50,2	5.115	50	225
31500513	13	36	18	84,9	8.650	50	380
31500705	5	18,5	7	12,5	1.275	100.	50
31500706	6	18,5	8	18	1.835	100	75
31500708	8	24	10	32,1	3.270	100	135
31500710	10	28	14	50,2	5.115	100	225
31500713	13	36	18	84,9	8.650	100	380
31500716	16	45	22	128,6	13.100	100	570

**Roestvast stalen ketting**  
**Stainless chain**

**Roestvast stalen ketting / langschalmig**  
**Stainless chain / long link**

| DIN 763 / AISI-316 / niet voor hijsdoeleinden  
| DIN 763 / AISI-316 / not for lifting applications



d = diameter  
d = diameter

mbl = minimum breekkracht  
mbl = minimum breaking load


LB = lengte per bos  
LB = length per bundle

Artikelnr.	d	a	b	mbl	mbl	LB	kg/100m
Part no.	mm	mm	mm	kN	kg	m	kg/100m
31501002	2	22	4	1,3	130	50.	6
31501003	3	26	6	4,5	460	50	15
31501004	4	32	8	8	815	50	27
31501005	5	35	10	12,5	1.275	50	43
31501006	6	42	12	18	1.835	50	63
31501008	8	52	16	32,1	3.270	50	110
31501010	10	66	20	50,2	5.115	50	175
31501013	13	82	26	84,9	8.650	50	295
31501016	16	100	32	128,6	13.100	50	445

**Verzinkte ketting**  
**Galvanised chain**

**Electrolytisch verzinkte ketting / kortschalmig**  
**Electro galvanised chain / short link**

| DIN 766 / grade 30 / niet voor hijsdoeleinden  
| DIN 766 / grade 30 / not for lifting applications



d = diameter  
d = diameter


mbl = minimum breekkracht  
mbl = minimum breaking load

LB = lengte per bos  
LB = length per bundle

Artikelnr.	d	a	b	mbl	mbl	LB	kg/100m
Part no.	mm	mm	mm	kN	kg	m	kg/100m
31000103	3	16	5	4	410	30.	20
31000104	4	16	6	8	815	30	32
31000105	5	18,5	7	12,5	1.275	30	51
31000106	6	18,5	8	16	1.630	30	80
31000108	8	24	10	32	3.260	30	140
31000110	10	28	14	50	5.100	30	220
31000113	13	36	18	80	8.150	30	380

**Electrolytisch verzinkte ketting / langschalmig**  
**Electro galvanised chain / long link**

| DIN 763 / grade 30 / niet voor hijsdoeleinden  
| DIN 763 / grade 30 / not for lifting applications



d = diameter  
d = diameter

mbl = minimum breekkracht  
mbl = minimum breaking load


LB = lengte per bos  
LB = length per bundle

Artikelnr.	d	a	b	mbl	mbl	LB	kg/100m
Part no.	mm	mm	mm	kN	kg	m	kg/100m
31010103	3	26	6	3,5	355	30.	18
31010104	4	32	8	6,8	690	30	27
31010105	5	35	10	10	1.020	30	43
31010106	6	42	12	12	1.220	30	63
31010107	7	49	14	19	1.935	30	86
31010108	8	52	16	25	2.550	30	110
31010110	10	66	20	40	4.080	30	175
31010113	13	82	26	64	6.520	30	295

**Verzinkte ketting**  
**Galvanised chain**

**Vuurverzinkte ketting / kortschalmig**  
**Hot dipped galvanised chain / short link**

| DIN 766 / grade 30 / niet voor hijsdoeleinden  
| DIN 766 / grade 30 / not for lifting applications



d = diameter  
d = diameter

mbl = minimum breekkracht  
mbl = minimum breaking load


LB = lengte per bos  
LB = length per bundle

Artikelnr.	d	a	b	mbl	mbl	LB	kg/100m
Part no.	mm	mm	mm	kN	kg	m	kg/100m
31000203	3	16	5	4	410	30	20
31000204	4	16	6	8	815	30	32
31000205	5	18,5	7	12,5	1.275	30	51
31000206	6	18,5	8	16	1.630	30	80
31000207	7	22	9	25	2.550	30	100
31000208	8	24	10	32	3.260	30	140
31000210	10	28	14	50	5.100	30	220
31000213	13	36	18	80	8.150	30	380
31000216	16	45	22	125	12.740	30	580
31000220	20	56	28	200	20.400	30	900
31000406	6	18,5	8	16	1.630	100	80
31000408	8	24	10	32	3.260	100	140
31000410	10	28	14	50	5.100	100	220
31000413	13	36	18	80	8.150	100	380

## Verzinkte ketting Galvanised chain

**Vuurverzinkte ketting / langschalmig**  
**Hot dipped galvanised chain / long link**

| DIN 763 / grade 30 / niet voor hijsdoeleinden  
| DIN 763 / grade 30 / not for lifting applications



d = diameter  
d = diameter

mbl = minimum breekkracht  
mbl = minimum breaking load

LB = lengte per bos  
LB = length per bundle

Artikelnr.	d	a	b	mbl	mbl	LB	kg/100m
Part no.	mm	mm	mm	kN	kg	m	kg/100m
31010203	3	26	6	3,5	355	30.	18
31010204	4	32	8	6,8	690	30	27
31010205	5	35	10	10	1.020	30	43
31010206	6	42	12	12	1.220	30	63
31010207	7	49	14	19	1.935	30	86
31010208	8	52	16	25	2.550	30	110
31010210	10	66	20	40	4.080	30	175
31010213	13	82	26	64	6.520	30	295
31010216	16	100	32	105	10.700	30	445
31010220	20	120	35	160	16.300	30	695

## Afzetketting Signal chain / fence chain

### Verzinkte afzetketting Galvanised signal chain for fencing

| Gekleurd / niet voor hijsdoeleinden  
| Coloured / not for lifting applications




d = diameter  
d = diameter

kl = kleur  
kl = colour

LB = lengte per bos  
LB = length per bundle

Artikelnr.	d	a	b	kl	LB	kg/100m
Part no.	mm	mm	mm	kl	m	kg/100m
31161005	5	35	10	rood-wit / red-white	30.	43
31161006	6	42	12	rood-wit / red-white	30	63
31161406	6	42	12	geel-zwart / yellow-black	30	63



### Kunststof afzetketting Plastic signal chain for fencing

| Gekleurd / niet voor hijsdoeleinden  
| Coloured / not for lifting applications




d = diameter  
d = diameter

kl = kleur  
kl = colour

LB = lengte per bos  
LB = length per bundle

Artikelnr.	d	a	b	kl	LB	kg/100m
Part no.	mm	mm	mm	kl	m	kg/100m
31162006	6	40	10	rood-wit / red-white	30	6
31162008	8	48	14	rood-wit / red-white	25	9,6
31162406	6	40	10	geel-zwart / yellow-black	25	6
31162408	8	48	14	geel-zwart / yellow-black	25	9,6



**Victorketting**  
**Knotted chain**


**Vuurverzinkte victorketting**  
**Hot dipped galvanised knotted chain**

| DIN 5686 / niet voor hijsdoeleinden  
| DIN 5686 / not for lifting applications



d = diameter  
d = diameter

LB = lengte per bos  
LB = length per bundle



Artikelnr.	Type	d	a	b	LB	kg/100m
Part no.		mm	mm	mm	m	kg/100m
313300020RS	K22	2,0	28	9	30	9
313300025RS	K27	2,5	35	11	30	14
313300028RS	K30	2,8	39	12,5	30	17
313300034RS	K35	3,4	44	15,5	30	26
313300046RS	K50	4,6	58	20,5	30.	50


**Roestvast stalen victorketting**  
**Stainless steel knotted chain**

| DIN 5686 / AISI-316 / niet voor hijsdoeleinden  
| DIN 5686 / AISI-316 / not for lifting applications



d = diameter  
d = diameter

LB = lengte per bos  
LB = length per bundle



Artikelnr.	Type	d	a	b	LB	kg/100m
Part no.		mm	mm	mm	m	kg/100m
312010016	K16	1,6	23	7	30	5,5
312010018	K18	1,8	25	8	30	7
312010020	K22	2,0	28	9	30	9
312010025	K27	2,5	35	11	30	14
312010028	K30	2,8	40	13	30.	17



**Matrasketting**  
**Mattress chain**

**Vuurverzinkte matrasketting**  
**Hot dipped galvanised mattress chain**

| Niet voor hijsdoeleinden / emmers a 100 meter  
| Not for lifting applications / 100 metres per bucket



d = diameter  
d = diameter

lpe = lengte per emmer  
lpe = length per bucket

Artikelnr.	d	lpe	kg/100m
Part no.	mm	m	kg/100m
3140141002	2,0	100	10,0

## Containerketting Lashing chain

**Containerketting / grade 80 / gelakt**  
**Lashing chain / grade 80 / painted**

| Niet voor hijsdoeleinden  
| Not for lifting applications



d = diameter  
d = diameter

mbl = minimum breekkracht  
mbl = minimum breaking load

LB = lengte per bos  
LB = length per bundle

Artikelnr.	Type	d	a	b	mbl	mbl	LB	kg/100m
Part no.		mm	mm	mm	kN	kg	m	kg/100m
31011711	lang / long	11	72	19	147	15.000	150	210
31011713	lang / long	13	80	23	196	20.000	150.	270
31012016	half-lang / semi-long	16	62	22	315	32.200	150	500
31012019	half-lang / semi-long	19	76	23	445	45.400	150.	700

